


MAXHUB UC P30

The MAXHUB UC P30 is a 4K dual-eye tracking camera designed for medium and large rooms. It features a built-in dual 4K camera and a range of AI-driven features, including Auto Framing, Speaker Tracking, and Presenter Tracking, which allow it to reproduce every moment and detail precisely. The camera supports a 4K video stream, captures every detail of the meeting, and offers multiple installation options for flexibility.




Dual Lens 4K Camera

120° FOV wide angle lens detects participants in real-time while directing the PTZ Camera with best view.



12x Optical Zoom

The 12X optical zoom, powerful 8MP camera and 4K resolution offer the range and picture quality to produce the highest quality output.



AI Powered

Auto Framing
Speaker Tracking
Presenter Tracking



Manage And Control

Remotely manage and control via MAXHUB Pivot or room control on MAXHUB Microsoft Teams Rooms products.



Privacy Guarantee

When not in use, PTZ camera tilts downward and electric privacy cover would remain closed.



Flexible Installation

With PoE+, a single Cat5e/Cat6e cable supports IP Streaming and power.

UC P30

Dual Camera	
PTZ Camera	
Image sensor	Sony 4K, 1/1.8, 8.42M pixel
Aperture	F1.8
Video outputs (USB 3.0)	H.264/MJPEG up to 2160p@30fps YUV up to 1080p@30fps
Video outputs (USB 2.0)	H.264/MJPEG up to 1080p@30fps ;
Video outputs (HDMI)	H.264/MJPEG up to 2160@30fps ;
Video outputs (IP)	H.264/MJPEG up to 2160p@30fps (first stream) H.264/MJPEG up to 72p@30fps (second stream)
Optical zoom	12 x
Digital zoom	16 x
FOV	DFOV 90°/ HFOV 80°/ VFOV 49.2°
Lens focal length	4.8mm ~ 57.8mm
Lens F#	1.8 ~ 3.6
Motorized Pan & tilt	Pan: ±170°, Tilt: ±90°;
Preset number	10 via IR remote, 128 via RS232
Image flip and image mirror	Yes
Panoramic Camera	
8MP, Sony Sensor	
120° DFOV	
Manual Tilt: ± 10°	
Electric Privacy Cover	
Camera LED Indicator	
AI Feature	
Auto Framing	
Speaker Tracking	
Presenter Tracking	
Intelligent Focus	
IO Ports	
USB 3.0 Type-C (Device)	× 1
USB 2.0 Type-A (Host)	× 1
Mic in (3.5mm)	× 1
HDMI 1.4 out	× 1
RJ45 (IP Steam, POE+)	× 1
RS232 (VISCA/Pelco-D/Pelco-P Protocol)	× 1
Security Lock Slot	× 1
Package Contents	
UC P30	× 1
USB C-A Cable (5m)	× 1
Power Adapter	× 1
Remote Control	× 1
Mounting Kits	× 1
Quick Start Guide	× 1
Power	
Power supply	DC In 12V, 2A / POE+ In (Max 25W)
Power consumption	~ 22W
Mechanical Specification	
Product Dimension	181 × 151.5 × 178.4 mm / 7.13 × 5.96 × 7.02 inch
Package Dimension (1pcs)	295 × 245 × 243 mm / 11.61 × 9.65 × 9.57 inch
Package Dimension (4pcs)	610 × 510 × 265 mm / 24.02 × 20.08 × 10.43 inch
Net Weight (1pcs)	2.3 kg / 5.34 lbs
Gross Weight (1pcs)	3.95 kg / 8.71 lbs
Gross Weight (4pcs)	16.9 kg / 37.26 lbs



To learn more, please scan the QR code or contact your LDI Connect Account Representative.

myLDI.com | New York | New Jersey | Connecticut | Southern California